

Intergrain Colour Additive

AU_DW02831

Description

Intergrain Colour Additive is a tint concentrate for adding colour to Intergrain Universal™ Timber Oil. Refer to Intergrain Universal Timber Oil instructions for surface preparation and application instructions.

Uses

Adds colour to Intergrain Universal Timber Oil.

Precautions And Limitations

Final colour depends on a number of factors including raw timber colour, porosity and application rate. Always test colour in an inconspicuous area before completing your project.

Typical Properties

Colour	Range of colours
Clean Up	Other: Mineral Turpentine
Clean Up Description	WARNING: To avoid spontaneous combustion of contaminated application cloths, soak application cloths in water or immediately spread used application cloths flat in a cool, well ventilated area to dry completely before disposal. Do not scrunch up or place cloths on top of each other.

Application Guide

Surface Preparation	<ul style="list-style-type: none"> Refer to Intergrain Universal Timber Oil instructions.
Application Procedure And Equipment	<ul style="list-style-type: none"> Refer to Intergrain Universal Timber Oil instructions.

Health And Safety			
MSDS Number	DLXGHSEN003789	Using Safety Precautions	Flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. Keep out of reach of children. Read label before use. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and all other equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust, fume, gas, mist, vapours or spray. Wash hands, face and all exposed skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective clothing, gloves, eye/face protection and suitable respirator.
Health Effects	<p>FIRST AID: If poisoning occurs, contact a Doctor or Poisons Information Centre (Phone Australia 131 126; New Zealand 0800 764 766). If medical advice is needed, have product container or label at hand.</p> <p>SWALLOWED: If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical advice.</p> <p>EYE: If in eyes, hold eyes open, flood with water for at least 15 minutes and see a doctor.</p> <p>SKIN: If skin contact occurs, remove contaminated clothing and wash skin thoroughly. If irritation occurs seek medical advice.</p> <p>INHALED: Remove from contaminated area. Apply artificial respiration if not breathing. Seek medical advice.</p>	Flammability	Flammable liquid and vapour.
Fire Suppression	If material is involved in a fire use alcohol resistant foam, standard foam or dry agent (carbon dioxide, dry chemical powder).	Protective Equipment	Wear protective clothing, gloves, eye/face protection and suitable respirator.
Storage	Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. Keep container tightly closed.	Disposal	Refer to Local Authority for disposal advice. Do not empty into drains and waterways.
Other	<p>Spills & Leaks: Clear area of all unprotected personnel. Slippery when spilt. Wear protective equipment. Absorb with sand or soil. Collect and seal in properly labelled drums. Refer to State/Territory Land Waste Management Authority for disposal.</p> <p>DO NOT REUSE CONTAINER. SEE THE SAFETY DATA SHEET FOR ADDITIONAL INFORMATION. IN A TRANSPORT EMERGENCY DIAL 000 POLICE OR FIRE BRIGADE</p> <p>EMERGENCY INFORMATION (ALL HOURS): AUST – 1800 033 111; NZ – 0800 734 607.</p> <p>CONTAINS: <60% NAPHTHA, PETROLEUM, HYDROTREATED HEAVY, <30% XYLENE, <1% METHYL ETHYL KETOXIME, <1% NONANE.</p>		
In the case of emergency, please call 1800 033 111			

Transport And Storage			
Shipment Name	PAINT	Flash Point	>23C
UN Number	1263	Dangerous Goods Class	3
Package Group	II		

Disclaimer

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427