

Intergrain Liquid 8 Timber Stripper

AU_DW02030

Part A	552W0172
--------	----------

Description

Intergrain Liquid 8 Timber Stripper is a fast acting, easy to use, water soluble gel timber finish and paint remover. Liquid 8 Timber Stripper is suitable for interior and exterior application. The N-Methylpyrrolidone (NMP) and Methylene Chloride (MV)+ Free formula has been specifically developed for safer interior usage. With excellent softening and deep penetration that allows multiple layers to be stripped in a single application, Liquid 8 Timber Stripper quickly and effectively removes most water and oil based timber coatings including acrylics, polyurethanes and varnishes. Note: Not suitable for epoxies and 2-Pack oil based coatings.

#^ENVIRONMENTALLY RESPONSIBLE

Liquid 8 Timber Stripper is free from Methylene Chloride and NMP which are found in most traditional paint and varnish strippers. This makes Liquid 8 Timber Stripper safer for interior usage, and gentler on the environment when compared to these traditional strippers.

Features

- N-Methylpyrrolidone (NMP) and Methylene Chloride free.
- Excellent softening and deep penetration.

Benefits

- Safer to use.
- Strips multiple layers in a single application.



Uses

Use on all interior and exterior timber surfaces. Note: Do not use on plastic surfaces, vinyl, masonite or rubber.

Precautions And Limitations

USE IN A WELL VENTILLATED AREA. AVOID SKIN AND EYE CONTACT. WEAR PROTECTIVE GLOVES AND GLASSES.
Not suitable for epoxies and 2-Pack oil based coatings.
Some oil based coatings will continue to bubble and strip even after the stripper has been removed.

Typical Properties

Clean Up	 Water																				
Application Method	 Brush																				
Application Conditions	<table border="1"> <thead> <tr> <th></th> <th>Min</th> <th>Max</th> <th>Recommended</th> </tr> </thead> <tbody> <tr> <td>Wet Film Per Coat (microns)</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Dry Film Per Coat (microns)</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Recoat Time (min)</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Theoretical Spread Rate (m²/L)</td> <td></td> <td></td> <td>0.5</td> </tr> </tbody> </table>		Min	Max	Recommended	Wet Film Per Coat (microns)				Dry Film Per Coat (microns)				Recoat Time (min)				Theoretical Spread Rate (m ² /L)			0.5
	Min	Max	Recommended																		
Wet Film Per Coat (microns)																					
Dry Film Per Coat (microns)																					
Recoat Time (min)																					
Theoretical Spread Rate (m ² /L)			0.5																		
Typical Properties Notes	<p>COVERAGE Approximately 0.5 square meters per litre when applied 2mm thick on a horizontal surface.</p>																				

Application Guide	
Application Procedure And Equipment	<ul style="list-style-type: none"> ▪ IMPORTANT: USE IN A WELL VENTILLATED AREA. AVOID SKIN AND EYE CONTACT. WEAR PROTECTIVE GLOVES AND GLASSES. Apply a thick coat by broad synthetic bristle brush. Do not exceed coverage rates. Take care on vertical or overhanging surfaces as Liquid 8 Timber Stripper may drip. Allow 15-20 minutes to penetrate and soften or wrinkle the coating. Stripping times will vary depending on the type of finish, thickness of the coating to be removed, and age of coating. Test with a scraper to ensure that the coating is easily removed. Remove using a paint scraper or if appropriate a high pressure water cleaner. On timber surfaces, work in the direction of the grain. On curved or rough surfaces or mouldings use a synthetic hard bristle brush or scourer. Important: The stripper remains active while in a wet state. Do not allow Liquid 8 Timber Stripper or softened or wrinkled coating to dry on the surface. For best results cover with a plastic drop sheet to stop Liquid 8 Timber Stripper from drying out and work in small areas at a time. Note: Some oil based coatings will continue to bubble and strip even after the stripper has been removed. Thick or stubborn coatings may require more than one application. Clean stripped surfaces thoroughly with water and allow to dry. Sand as necessary to remove any residue and any grain raise before refinishing the surface.

Health And Safety			
MSDS Number	DLXAUSEN000842	Using Safety Precautions	Keep out of reach of children. Avoid contact with skin and eyes or breathing vapour and spray mist (dust). Wear waterproof gloves and safety glasses. Use only in well ventilated areas. Wash hands after use. Slippery when spilt; clean up immediately.
Health Effects	<p>FIRST AID: If poisoning occurs, contact a Doctor or Poisons Information Centre (AUST: 131 126; NZ 0800 764 766).</p> <p>SWALLOWED: Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water.</p> <p>EYE: If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by Poisons Information Centre or a doctor, or for at least 15 minutes.</p> <p>INHALED: Remove from contaminated area.</p> <p>EMERGENCY INFORMATION (ALL HOURS): AUST – 1800 033 111; NZ – 0800 734 607</p>	Fire Suppression	If involved in a fire use water fog, foam or dry agents. Avoid breathing products of combustion.
Protective Equipment	Wear waterproof gloves and safety glasses.	Storage	Keep out of reach of children.
Disposal	Slippery when spilt; clean up immediately. Refer to Local Authority for disposal advice. Do not empty into drains and waterways. Do not reuse container.		
In the case of emergency, please call 1800 033 111			

Transport And Storage	
Pack A	552W0172
Size 1L 4L	Weight 1.3kg 4.8kg

Disclaimer

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427