

Intergrain UltraFloor Slip Resistant

AU_DW02546

Part A	521W0323
---------------	----------





<p>Description</p> <p>Intergrain UltraFloor SlipResistant allows you to easily meet slip resistance requirements for your interior timber floors, stairs, ramps or landings. UltraFloor SlipResistant does not require an additive, allowing you to exceed P4 and meet P5 slip resistance requirements in just three simple coats. UltraFloor SlipResistant is low odour and fast drying, enabling projects to be finished within one day.</p> <p>#ENVIRONMENTALLY RESPONSIBLE: Being water based, UltraFloor SlipResistant emits significantly less VOC's (volatile organic compounds)</p>
--

<p>Features</p> <ul style="list-style-type: none"> ▪ Slip resistant coating. ▪ Exceeds P4 slip resistance requirements. ▪ Exceptionally durable. ▪ Water based.
--

<p>Uses</p> <p>Interior timber floors, stairs, ramps and landings.</p>

<p>Precautions And Limitations</p> <p>Do not apply in temperatures above 35°C or below 10°C.</p>

Performance Guide			
Weather	Interior only.	Heat Resistance	Up to 100C
Water	Very good	Abrasion	Very good

Typical Properties																											
Gloss Level	Satin	Thinner	UltraFloor SlipResistant does not require thinning.																								
Colour	Clear, Colourless	Components	1																								
Number Of Coats	3	V.O.C. Level	<70g/L																								
Meets GBCA VOC Requirement?	Yes. Total Volatile Organic Content (TVOC) values are calculated in accordance to the stated methodology within Green Star Technical Manuals. The TVOC content is theoretically calculated as the sum total of the known VOC values of the product's raw material components. These materials include the base paint plus additional low VOC tinter required for non-factory packaged colours.	Sanding Properties	DO NOT SAND BETWEEN COATS																								
Touch Dry	2 hours																										
Clean Up	 Water																										
Application Method	   Brush Roller Pad																										
Application Conditions	<table border="0" style="width: 100%;"> <tr> <td style="text-align: center;">Solids By Volume</td> <td style="text-align: center;">31</td> <td></td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">Min</td> <td style="text-align: center;">Max</td> <td style="text-align: center;">Recommended</td> </tr> <tr> <td>Wet Film Per Coat (microns)</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Dry Film Per Coat (microns)</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Recoat Time (min)</td> <td style="text-align: center;">4 hours</td> <td></td> <td></td> </tr> <tr> <td>Theoretical Spread Rate (m²/L)</td> <td style="text-align: center;">10</td> <td style="text-align: center;">12</td> <td></td> </tr> </table>			Solids By Volume	31				Min	Max	Recommended	Wet Film Per Coat (microns)				Dry Film Per Coat (microns)				Recoat Time (min)	4 hours			Theoretical Spread Rate (m²/L)	10	12	
Solids By Volume	31																										
	Min	Max	Recommended																								
Wet Film Per Coat (microns)																											
Dry Film Per Coat (microns)																											
Recoat Time (min)	4 hours																										
Theoretical Spread Rate (m²/L)	10	12																									
Typical Properties Notes	COVERAGE: 10-12 square metres per litre depending on the porosity of the timber. DRYING TIME: All drying times are at 25°C and 50% humidity. Touch Dry: 2 hours. Recoat: Allow a minimum of 4 hours drying between coats. Cold or humid conditions will require longer. Floors will take light foot traffic after 12 hours, and normal foot traffic after 72 hours. Full curing 7 days. Replace furniture after 7 days. DRYING TIMES WILL BE LONGER IN CONDITIONS COOLER THAN 25°C OR MORE HUMID THAN 50% HUMIDITY.																										

Application Guide	
Surface Preparation	<ul style="list-style-type: none"> NEW BARE TIMBER Sand timber to an even, smooth surface. Clean oily timbers such as Brushbox, Spotted Gum, Cypress and Tallowwood with methylated spirits and allow to dry. Prepare cork in accordance with cork manufacturer's specifications. <p>PREVIOUSLY FINISHED SURFACES Remove any polishes with an appropriate floor stripper. Wash the surface using Cabot's® Floor Clean™ and allow to dry. Sand to a uniform dull finish. Vacuum and wipe off dust. Check for adhesion by applying UltraFloor SlipResistant to a small test area. Allow to dry for 24 hours then firmly press a strip of sticky tape over the coating and rip off quickly. If the coating is removed, sand the full surface back to bare timber. If the coating is not removed, sand the test area back to the dull finish.</p> <p>Note: If patches of the previous coating have worn back to expose bare timber, the full floor must be sanded back to bare timber.</p> <p>Nail holes and surface defects should be filled with Intergrain Woodblend™ Wood Filler after the first coat of UltraFloor SlipResistant. Do not use Linseed Oil putty. Ensure the surface is dry and free from dust, dirt, wax, polish and oil.</p>
Application Procedure And Equipment	<ul style="list-style-type: none"> Stir thoroughly before and during use with a flat blade stirrer. Do not thin. Cut in around edges with a narrow brush or applicator. Apply an even, generous coat with a lambswool applicator, short nap roller or quality long bristle brush. Work along the complete length of three to four boards at a time, keeping a wet edge to prevent lapping or join marks. Lay off lightly in the direction of the grain. Do not overwork the coating as this will result in a patchy, uneven finish. Allow a minimum of four hours to dry. Apply two more coats as above. 3 coats are required to exceed P4 and meet P5 slip resistance standards. Do not sand between coats. <p>MAINTENANCE: Do not apply wax or polish over UltraFloor SlipResistant. Regularly clean floors with Cabot's Floor Clean. Surfaces should be recoated before UltraFloor SlipResistant has worn away to expose bare timber, or slip resistance has reduced. Sand to a uniform dull surface and wipe away dust. Apply one to two coats following application instructions. If patches of floor have been worn back to bare timber, the coating must be fully removed by sanding and the surface prepared as per instructions for new timber.</p>

Health And Safety			
MSDS Number	DLXGHSEN003206	Using Safety Precautions	Keep out of reach of children. Avoid contact with skin and eyes or breathing vapour and spray mist (dust). Wear waterproof gloves and safety glasses. Use only in well ventilated areas. Wash hands after use.
Health Effects	<p>FIRST AID: If poisoning occurs, contact a Doctor or Poisons Information Centre (AUST: 131 126; NZ 0800 764 766).</p> <p>SWALLOWED: Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water.</p> <p>EYE: If in eyes, hold eyes open, flush with running water for at least 15 minutes.</p> <p>SKIN: If skin contact occurs, remove contaminated clothing and wash skin thoroughly.</p> <p>INHALED: Remove from contaminated area.</p>	Flammability	This product is not flammable.
Fire Suppression	If involved in a fire use water fog, foam or dry agents. Avoid breathing products of combustion.	Storage	Keep out of reach of children.
Disposal	<p>FOR SPILLS & DISPOSAL Slippery when spilt; clean up immediately. Refer to Local Authority for disposal advice. Do not empty into drains and waterways. Do not reuse container. For more information on responsible disposal of paint and packaging visit paintback.com.au In New Zealand visit painttakeback.co.nz</p>		
In the case of emergency, please call 1800 033 111			

Transport And Storage	
Pack A	521W0323
Size 1L	Weight 1.188Kg

Disclaimer

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427