

Intergrain UltraPrep Mould Killer

AU_DW02640


Part A	552W0337
--------	----------

<p>Description</p> <p>Intergrain UltraPrep Mould Killer is a biodegradable, environmentally responsible formula with an active mould killing life of 6 hours once diluted. Specially formulated to effectively remove mould from exterior timber including coated and uncoated surfaces.</p> <p>Note: Lack of visible growth does not necessarily indicate an uncontaminated surface. Many spores are not visible to the naked eye and can germinate and grow beneath surface coatings and timber stains. It is recommended to always use Intergrain UltraPrep Mould Killer in humid and mould susceptible areas as the first step of preparing timber for coating.</p>
--

<p>Features</p> <ul style="list-style-type: none"> Free from hypochlorite bleach Specially formulated for use on timber
--

<p>Uses</p> <p>On all exterior timber that may be susceptible to, or already contaminated by mould.</p>
--

<p>Precautions And Limitations</p> <p>Once powder has been diluted, use within 6 hours.</p>
--

Typical Properties			
V.O.C. Level	0g/L	Meets GBCA VOC Requirement?	Yes. Total Volatile Organic Content (TVOC) values are calculated in accordance to the stated methodology within Green Star Technical Manuals. The TVOC content is theoretically calculated as the sum total of the known VOC values of the product's raw material components. These materials include the base paint plus additional low VOC tinter required for non-factory packaged colours.
Clean Up	 Water		
Typical Properties Notes	<p>MIX RATIO 100g/L of water</p> <p>COVERAGE Up to 20m²/800g when mixed</p>		

Application Guide	
Application Procedure And Equipment	<ul style="list-style-type: none"> Mix 800g of Intergrain UltraPrep Mould Killer into 8L of water, stir until powder is fully dissolved. Warm water will help dissolve the powder faster. Scrub on to entire area with a stiff bristle brush. Leave for 15 minutes, do not allow to dry on the timber, add more product if required to keep it wet. <p>Rinse off exterior surfaces thoroughly using maximum pressure from a garden hose or use a high pressure water cleaner. For best results, a high pressure water cleaner is recommended.</p> <p>If any visible mould remains, repeat the process.</p> <p>Important: Once powder has been diluted, use within 6 hours. Any left over solution can be safely disposed of down a drain.</p>

Health And Safety			
MSDS Number	DLXGHCEN003394	Using Safety Precautions	Keep out of reach of children. Read label before use. Wash hands, face and all exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective clothing, gloves, eye/face protection and suitable respirator. Slippery when spilt.
Health Effects	FIRST AID: If poisoning occurs, contact a Doctor or Poisons Information Centre (Phone Australia 131 126; New Zealand 0800 764 766). If medical advice is needed, have product container or label at hand. SWALLOWED: If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical assistance. EYE: If in eyes, hold eyes open, flood with water for at least 15 minutes and see a doctor. SKIN: If skin contact occurs, remove contaminated clothing and wash skin thoroughly. If irritation occurs seek medical advice. INHALED: Remove from contaminated area. Seek medical advice.	Flammability	Non-flammable
Fire Suppression	If material is involved in a fire use water fog (or if unavailable fine water spray), alcohol resistant foam, standard foam, dry agent (carbon dioxide, dry chemical powder).	Protective Equipment	Wear protective clothing, gloves, eye/face protection and suitable respirator.
Storage	Keep out of reach of children.	Other	CONTAINS: >60% SODIUM CARBONATE, 10-30% CARBONIC ACID, DISODIUM SALT, COMPOUND WITH HYDROGEN PEROXIDE (H2O2) (2:3)
In the case of emergency, please call 1800 033 111			

Transport And Storage	
Pack A	552W0337
Size 800g	Weight 800g

Disclaimer

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.
 DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427