

Intergrain Industrial Primer Water Based Biscuit

AU_DW02485

Part A	701W0315
--------	----------

Description

Intergrain Industrial Primers are water based coatings designed for use on timber as factory applied primers. They provide short term protection for timber against marking during handling in the factory and during transport. They must be finish coated within 3 months after installation. Intergrain Industrial Primers can be applied by brush, roller or spray equipment.

Intergrain Industrial Primer Water Based Biscuit is a light tan coloured, short term interior/exterior opaque tannin blocking primer.

Features

- Water based.
- Apply by brush, roller or spray.
- Tannin blocking.

Benefits

- Fast drying and low odour.
- Versatile.






Uses

Factory application onto all timber.

Performance Guide

Weather	Not designed as a finish coat.	Heat Resistance	Softens in temperatures over 70C.
----------------	--------------------------------	------------------------	-----------------------------------

Typical Properties

Gloss Level	Low sheen	Thinner	Water																								
Colour	Light yellow-brown	Components	1																								
Number Of Coats	1-2	V.O.C. Level	< 60g/L																								
Touch Dry	30 minutes																										
Clean Up	 Water																										
Application Method	 Air Spray  Airless Spray  Brush  Roller																										
Application Conditions	<table> <tr> <td>Solids By Volume</td><td>38</td><td></td><td></td></tr> <tr> <td></td><td>Min</td><td>Max</td><td>Recommended</td></tr> <tr> <td>Wet Film Per Coat (microns)</td><td></td><td></td><td>63</td></tr> <tr> <td>Dry Film Per Coat (microns)</td><td></td><td></td><td>24</td></tr> <tr> <td>Recoat Time (min)</td><td>2 hours</td><td></td><td></td></tr> <tr> <td>Theoretical Spread Rate (m²/L)</td><td></td><td></td><td>16</td></tr> </table>			Solids By Volume	38				Min	Max	Recommended	Wet Film Per Coat (microns)			63	Dry Film Per Coat (microns)			24	Recoat Time (min)	2 hours			Theoretical Spread Rate (m²/L)			16
Solids By Volume	38																										
	Min	Max	Recommended																								
Wet Film Per Coat (microns)			63																								
Dry Film Per Coat (microns)			24																								
Recoat Time (min)	2 hours																										
Theoretical Spread Rate (m²/L)			16																								
Typical Properties Notes	DRY TIMES These dry times are based on drying conditions of 25°C and 50% relative humidity. Dry times will be subject to climatic conditions, film thickness and airflow.																										

Application Guide

Surface Preparation	<ul style="list-style-type: none"> Ensure surface is dry and free from dirt, dust, grease, oil and loose material. Sand to a smooth surface if necessary. Remove all sanding dust.
Application Procedure And Equipment	<ul style="list-style-type: none"> Apply 1-2 coats using brush, roller or spray equipment. If spraying, the product can be thinned with water, as required, to suit spray equipment. <p>VISCOSITY 300 cps - 600 cps 300 mPa s - 600 mPas</p>

Health And Safety

Using Safety Precautions	Avoid contact with skin and eyes. Avoid breathing dust, fume, gas, mist, vapour or spray. Wear overalls, safety shoes, impervious gloves and safety glasses. Use only in well ventilated areas. Wash hands after use. Keep containers closed when not in use.	Health Effects	<p>FIRST AID: If poisoning occurs, contact a Doctor or Poisons Information Centre (Phone Australia 131 126; New Zealand 0800 764 766). If medical advice is needed, have product container or label at hand.</p> <p>SWALLOWED: If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical advice.</p> <p>EYE: If in eyes, hold eyes open, flood with water for at least 15 minutes and see a doctor.</p> <p>SKIN: If skin contact occurs, remove contaminated clothing and wash skin thoroughly. If irritation occurs seek medical advice.</p> <p>INHALED: Remove from contaminated area. Seek medical advice.</p>
Flammability	Non-flammable	Fire Suppression	If material is involved in a fire use water fog (or if unavailable fine water spray), alcohol resistant foam, standard foam, dry agent (carbon dioxide, dry chemical powder).
Protective Equipment	Wear overalls, safety shoes, impervious gloves and safety glasses	Disposal	Refer to State/Territory Land Waste Management Authority for disposal.
Other	Emergency Tel: Australia – 1800 033 111 New Zealand – 0800 734 607		

In the case of emergency, please call 1800 033 111

Transport And Storage

Pack A	701W0315
Size 200L	Weight 260Kg

Disclaimer

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427