

Introducing new Intergrain® Enviropro® Timberseal Alcohol Based.

Intergrain® Enviropro® Timberseal™ Alcohol Based

- Timber floor & parquetry sealer
- ENHANCES the colour & grain of timber floors
- Dries fast – 1 hour
- Easy to use
- Lower odour than traditional solvent based sealers
- Topcoat with Water Based Enviropro® Endure® 1 Pack, Enviropro® Endure® 2 Pack or Enviropro® Endure® High Build
- Name Change – Timberseal™ now called Timberseal™ Water Based

See back of flyer for system map



Directions

Use on	Timber & parquetry floors	Recoat Time	1 Hour
Mixing	Shake bottle for 1 minute	Sanding	We do not recommend sanding Timberseal™ Alcohol Based – sand after your first topcoat is dry
Roller	10mm nap microfiber roller	Suitable Topcoats	Enviropro® Endure® 1 Pack, Enviropro® Endure® 2 Pack, Enviropro® Endure® High Build
Touch Dry	30 minutes	Clean up	Methylated Spirits



Australian Owned and Operated

To contact Enviropro®, please call 1800 630 285
or contact your Account Manager.

Intergrain, Enviropro and Endure are registered trade marks. Timberseal is a trade mark.

Intergrain®
enviropro®

The new Enviropro® Complete Control System.

1 Select your sealer

Enviropro® Timberseal™ Water Based

- MAINTAINS the natural colour & grain of timber
- Dries fast – 1 hour
- Easy to use



OR

Enviropro® Timberseal™ Alcohol Based

- ENHANCES the natural colour & grain of timber
- Dries fast – 1 hour
- Easy to use



2 Select your top coat & sheen

Enviropro® Endure® 1 Pack

- Highly durable
- Resistant to everyday wear and tear
- Maintains the natural look of timber



Matt, Satin or Gloss

OR

Enviropro® Endure® 2 Pack

- Extremely durable
- Resistant to commercial levels of foot traffic, wear and tear
- Maintains the natural look of timber



Matt, Satin or Gloss

Note: While a sealer is not required, either Timberseal can be used under Endure® High Build.

www.intergrain.com.au/professional-floor-finishes

Intergrain, Enviropro and Endure are registered trade marks. Timberseal is a trade mark.

Intergrain
enviropro®