

Intergrain Industrial Timber Oil Water Based Primer

AU_DW02482

Part A	701W0311
---------------	----------


Description
Intergrain Industrial Timber Oil Water Based Primer is a lightly pigmented, penetrating water-based exterior oil. It is designed for industrial application through brushing machines or vacuum coaters.

Features
Highly penetrating, fast drying, low odour.

Benefits
Excellent foundation for any site applied system other than mineral oil based products.

Uses
Industrial application onto all exterior timber.

Performance Guide			
Weather	Must be over coated with a suitable exterior coating.	Heat Resistance	Softens in temperatures over 70C

Typical Properties			
Gloss Level	Matt	Colour	Light brown
Components	1	Number Of Coats	At least 1
V.O.C. Level	< 10g/L	Meets GBCA VOC Requirement?	Yes. Total Volatile Organic Content (TVOC) values are calculated in accordance to the stated methodology within Green Star Technical Manuals. The TVOC content is theoretically calculated as the sum total of the known VOC values of the product's raw material components. These materials include the base paint plus additional low VOC tinter required for non-factory packaged colours.
Touch Dry	30 minutes		
Clean Up	 Water		
Application Method	Other: Vacuum Coater, Brushing Machine		
Application Conditions	Solids By Volume	10	
		Min	Max Recommended
	Wet Film Per Coat (microns)		
	Dry Film Per Coat (microns)		
	Recoat Time (min)		
	Theoretical Spread Rate (m²/L)		
Typical Properties Notes	DRYING TIME Drying times are given at 25°C and 50% relative humidity. Lower temperatures or higher humidity can lead to extended drying times.		
	COVERAGE Coverage rates are subject to variation depending on condition of timber, timber species and timber porosity.		

Application Guide

Surface Preparation	<ul style="list-style-type: none"> • Ensure substrate is clean, dry and free from dirt, dust, grease and grime.
----------------------------	--------------------------------------------------------------------------------------------------------------------------------

Health And Safety

MSDS Number	DLXGHSEN003173	Using Safety Precautions	Slippery when spilt. Avoid contact with skin and eyes. Avoid breathing dust, fume, gas, mist, vapour or spray. Wear overalls, safety shoes, impervious gloves and safety glasses. Use only in well ventilated areas. Wash hands after use. Keep containers closed when not in use.
Health Effects	<p>FIRST AID: If poisoning occurs, contact a Doctor or Poisons Information Centre (Phone Australia 131 126; New Zealand 0800 764 766). If medical advice is needed, have product container or label at hand.</p> <p>SWALLOWED: If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical advice.</p> <p>EYE: If in eyes, hold eyes open, flood with water for at least 15 minutes and see a doctor.</p> <p>SKIN: If skin contact occurs, remove contaminated clothing and wash skin thoroughly. If irritation occurs seek medical advice.</p> <p>INHALED: Remove from contaminated area. Seek medical advice.</p>	Flammability	Non-flammable.
Fire Suppression	If material is involved in a fire use water fog (or if unavailable fine water spray), alcohol resistant foam, standard foam, dry agent (carbon dioxide, dry chemical powder).	Protective Equipment	Wear overalls, safety shoes, impervious gloves and safety glasses.
Storage	Keep containers closed when not in use.	Other	Emergency Tel: Australia – 1800 033 111 New Zealand – 0800 734 607

In the case of emergency, please call 1800 033 111

Transport And Storage

Pack A	701W0311
Size	Weight
200L	222Kg

Disclaimer

Dulux, Selleys and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating/product systems.
 DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating/product systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Selleys" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427