

Intergrain®  
**enviropo**®




# Timber Floor Finishes

The Professional Floor Sander's Guide



**If you ever  
have an issue,  
we've got  
your back.**



**Need product to fix an issue?**

We'll supply it to you for free.



**Sanding required to fix an issue?**

We'll pay you to sand back.

**We're so confident in the Enviopro range that we guarantee its performance.**

\*Terms and conditions apply. See over for details, process and limitations. Full terms and conditions available in-store or [www.intergrain.com.au/downloads](http://www.intergrain.com.au/downloads).  
Confidence Guarantee only applicable to professional floor sanders.

# Sealers

## Timberseal™ Water Based

### Our go-to sealer

- Maintains the colour & grain of timber floors
- Dries fast – 1 hour
- Easy to use – not too thick, not too thin
- Do not sand



## Timberseal™ Alcohol Based

### Our easy sealing solution

- Enhances the colour & grain of timber floors
- Dries fast – 1 hour
- Easy to use
- Recommended for use on oily or tannin rich timbers
- Do not sand
- Topcoat with Water Based Endure® 1 Pack, 2 Pack or High Build



## Timberseal™ Ultra

### Our sandable, smooth application feel sealer

- Maintains the natural colour & grain of timber
- Dries fast – 1 hour
- Water based
- Suitable for use on most timber species
- Higher viscosity (thickness) for smooth application feel
- Must be sanded



# Top Coats

## Endure® 1 Pack

### Our no fuss 1 pack

- Maintains the natural look of timber
- Highly durable
- Resistant to everyday wear and tear
- Available in Matt, Satin and Gloss



## Endure® 2 Pack

### Our highest performer

- Maintains the natural look of timber
- Extremely durable
- Resistant to commercial levels of foot traffic, wear and tear
- Available in Matt, Satin and Gloss



## Endure® High Build

### Our unique two coat wonder

- Maintains the natural look of timber
- Resistant to everyday wear and tear
- No sealer required – only 2 coats
- Higher viscosity (thickness) for smooth application feel
- Available in Satin and Gloss



# Invisible Floor Finish

## Our new invisible hero

- Provides a finish with the appearance of bare wood
- Provides feel of natural timber
- Highly durable, with excellent scratch and stain resistance
- No sealer required (2 coat system)



Home owners will love:	Professional floor sanders will love:
✓ Natural, invisible sheen	✓ Can be applied over most existing floor finishes - no sanding required
✓ Provides appearance and feel of uncoated timber	✓ 2 coat system – no sealer required
✓ Protects timber floors from wear and tear	✓ Single pack product





# Top Coats

## Hard Wax Oil

### Your natural choice

- Highly durable
- 20-24m<sup>2</sup> coverage per litre
- 4 hour recoat time
- No sealer required
- 2 coat system



### Home owners will love:

✓ Natural matt finish	✓ Non-toxic when cured
✓ Maintains the wood texture and feel	✓ No sand maintenance – just clean and coat
✓ Highly durable, hard wearing finish	✓ EN71 certified – suitable for application onto children's toys



# Specialty

## Slip Resistant Endure® 2 Pack

### No-fuss slip resistance

- Mix A + B and apply
- Meets P4 & P5 standards
- Excellent wear resistance



## Squeaky Clean™

### Everyday cleaning solution

- Helps remove scuff marks
- Leaves a streak free finish
- Concentrated formula is simply diluted with water



## Wet Edge Extender

### Hot weather helper

- Add to water based sealers and topcoats to ease application in hot weather
- More working time
- Better levelling
- Reduces lap marking



## Quick Reference Table

	Product	Description	Sheen Levels	Apply with	Preparation	Coverage <sup>^</sup>	No. of Coats	Touch Dry <sup>*</sup>	Recoat Time <sup>*</sup>	Full Cure <sup>*</sup>	Clean Up With
Sealers	Timberseal™ Water Based	Water based sealer, suitable for timber floors and parquetry.	N/A	Brush or 10mm microfibre roller	Bare timber only	8-10m²/L	1	30 mins	1 hour	N/A	Water
	Timberseal™ Alcohol Based	Easy to use alcohol based sealing solution. Suitable for timber floors and parquetry.	N/A	Brush or 10mm microfibre roller	Bare timber only	8-10m²/L	1	30 mins	1 hour	N/A	Methelyated Spirits
	Timberseal™ Ultra	Sandable, smooth application feel timber sealer. Suitable for timber floors and parquetry.	N/A	Brush or 10mm microfibre roller	Bare timber only	8-10m²/L	1	30 mins	1 hour	N/A	Water
Top Coats	Endure® 1 Pack	Highly durable, no fuss 1 Pack.	Matt, Satin, Gloss	Brush or 10mm microfibre roller	Any Timberseal™ variant	8-10m²/L	2-3	2 hours	4 Hours	7 Days	Water
	Endure® 2 Pack	Extremely durable high performing 2 Pack.	Matt, Satin, Gloss	Brush or 10mm microfibre roller	Any Timberseal™ variant	8-10m²/L	2-3	2 hours	4 Hours	7 Days	Water
	Invisible Floor Finish	Highly durable 1 Pack that leaves timber looking and feeling uncoated.	Invisible	Brush or 10mm microfibre roller	Bare timber or previously coated surfaces (no sanding or sealer required)	8-10m²/L	1-2	2 Hours	4 Hours	5 Days	Water
	Endure® High Build	Unique two coat wonder – no sealer required.	Satin, Gloss	Brush or 12mm microfibre roller	*Optional* Any Timberseal™ variant	8-10m²/L	2-3	1 Hour	4 Hours	14 Days	Water
	Hard Wax Oil	Highly durable, natural look & feel timber oil.	Natural Matt	Brush or 10mm microfibre roller	Bare timber OR surfaces previously coated with Enviropro Hard Wax Oil	20-24m²/L	2	1 Hour	4 Hours	7 Days	Mineral Turpentine
	Slip Resistant Endure® 2 Pack	Simplified slip resistance - just mix A +B.	Low Satin	Brush or 10mm microfibre roller	Any Timberseal™ variant	8-10m²/L	2	2 hours	4 Hours	7 Days	Water
Additive	Wet Edge Extender	Hot weather helper – reduces lapmarks and makes hot weather application less stressful.	N/A	Mix thoroughly	N/A	Add to max. 5%	N/A	N/A	N/A	N/A	Water
Cleaner	Squeaky Clean™	Everyday timber floor cleaning solution for the home owner.	N/A	Damp mop	N/A	2 capfuls in 4L water	N/A	N/A	N/A	N/A	Water

[www.intergrain.com.au/professional-floor-finishes](http://www.intergrain.com.au/professional-floor-finishes)

Technical Assistance: 1800 630 285 | Datasheets: [www.duspec.com.au](http://www.duspec.com.au)

 **enviopro**

<sup>^</sup>Coverage rates are dependent on the porosity of the timber species, stated coverage rates must not be exceeded.

<sup>\*</sup>Drying times are based on drying conditions of 25C and 50% humidity. Variations from these conditions may extend or reduce drying times. Please refer to the application instructions provided on the pack before commencing coating.

<sup>\*\*</sup>Please review the terms and conditions document for a full understanding of our guarantee. To view Ts & Cs; [intergrain.com.au/downloads](http://intergrain.com.au/downloads), see in-store or contact your Enviopro Rep. Residential jobs only. No more than 50 litres of free product to be supplied per claim. If sanding is required - we cap payment at 200 square metres (\$2000). Claims must be brought to the attention of Enviopro within 5 days of product application. We reserve the right to immediately escalate any issue to a full technical investigation. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure. Confidence Guarantee only available to professional floor sanders in Australia.

© Intergrain, Enviopro and Endure are registered trade marks. ™ Squeaky Clean and Timberseal are trade marks.. Intergrain Timber Finishes, 1956 Dandenong Road, Clayton Victoria 3168.