

Intergrain Woodblend Putty

AUDW0770

Part A	927-line
---------------	----------

Description

Intergrain Woodblend is a water based timber and grain filler, suitable for both interior and exterior use. Woodblend has excellent durability, minimal shrinkage and low odour. It is easy to apply and sands to an extremely fine, smooth finish. Woodblend is suitable for use on all timber species and can be coated with water or oil based paints, stains and timber finishes. Woodblend is available in a range of popular timber colours which can be mixed to achieve custom shades.

ENVIRONMENTALLY RESPONSIBLE
Being water based, Woodblend emits significantly less VOC's (volatile organic compounds) into the atmosphere than traditional oil based putties. So, combined with being healthier to use, Woodblend is much gentler on the environment.

Features

- Waterbased
- Interior & exterior use
- A range of intermixable colours
- Sets firmly

Benefits

- Environmentally friendly
- Versatile
- Can match most timber colours
- Does not shrink or crack


Uses

Use on all interior and exterior timber surfaces including weatherboards, decking, flooring and furniture. Woodblend can be used to fill nail holes, splits, knot holes and as a grain filler to give a smooth finish to timber surfaces.

Performance Guide

Weather	Interior and exterior use
----------------	---------------------------

Typical Properties

Thinner	Water	Colour	6 packaged colours
Components	1	Number Of Coats	N/A
Toxicity	Lead free.	V.O.C. Level	< 110g/L
Shelf Life	Indefinite		
Clean Up	 Water		
Clean Up Description	Indefinite		
Application Method	Other: Putty knife		
Application Conditions	Min	Max	Recommended
	Wet Film Per Coat (microns)		
	Dry Film Per Coat (microns)		
	Recoat Time (min)	2 hours	
	Theoretical Spread Rate (m²/L)		
Typical Properties Notes	DRYING AND RECOAT TIME All timings quoted at 25C and 50% humidity. Drying and overcoating times will be retarded by cold or humid conditions. Deep holes may require longer.		

Application Guide	
Surface Preparation	<ul style="list-style-type: none"> Surface must be in sound condition, clean, dry and free from dust, grease, wax and oil. Indentations and holes must be clear of all loose material.
Application Procedure And Equipment	<ul style="list-style-type: none"> Apply Woodblend with a flexible filling blade or knife. Fill deep holes in approx. 10mm stages, allowing 2 hours drying time between each stage. To ease application, dampen blade with water. Wipe off excess with a slightly damp sponge. When dry, sand to a smooth finish. When using clear finishes, apply Woodblend after the first coat of clear to minimise smudging. For use as a grain filler, thin Woodblend with 5-10% water to achieve required consistency. Apply with a flexible filling blade or knife and allow to dry. When dry, sand back to bare timber, leaving filler only in the grain. <p>IMPORTANT: Keep container tightly closed when not in use.</p>

Health And Safety			
MSDS Number	14272813	Using Safety Precautions	Provide adequate ventilation. If using inside keep windows and doors open during use and while drying.
Health Effects	<p>For detailed information refer to product label and the current Material Safety Data Sheet available through INTERGRAIN Sales and Customer Service offices.</p> <p>FIRST AID: If poisoning occurs, contact a doctor or Poisons Information Centre. Phone 13 11 26.</p> <p>SWALLOWED: Give plenty of water to drink. Seek medical advice.</p> <p>EYE: Rinse with plenty of running water. Seek medical help if irritation occurs.</p>	Flammability	This product is non-flammable.
Protective Equipment	Wear eye protection, protective clothing and gloves.	Storage	Keep out of reach of children.
Disposal	Normally suitable for disposal at approved waste land sites.		
In the case of emergency, please call 1800 033 111			

Transport And Storage	
Pack A	927-line
Size	Weight
800 gm 100 gm	800 gm 100 gm

Disclaimer

Dulux and Other marks followed by ® are registered trademarks. Marks followed by the symbol of ™ are trademarks.

The data provided within the Duspec system is correct at the time of publication, however it is the responsibility of those using this information to check that it is current prior to specifying or using any of these coating systems.

DISCLAIMER: Any advice, recommendation, information, assistance or service provided by any of the divisions of DuluxGroup (Australia) Pty Ltd or its related entities (collectively, DuluxGroup) in relation to goods manufactured by it or their use and application is given in good faith and is believed by DuluxGroup to be appropriate and reliable. However, any advice, recommendation, information, assistance or service provided by DuluxGroup is provided without liability or responsibility PROVIDED THAT the foregoing shall not exclude, limit, restrict or modify the right entitlements and remedies conferred upon any person or the liabilities imposed upon DuluxGroup by any condition or warranty implied by Commonwealth, State or Territory Act or ordinance void or prohibiting such exclusion limitation or modification. Coating systems can be expected to perform as indicated on the Duspec Spec Sheet so long as applications and application procedures of the individual products are followed as recommended on the appropriate Product data Sheet. "DuluxGroup" "Dulux" "Berger" "Berger Gold Label" "Hadrian" "Walpamur" "Levene" "Acratex" and Other marks followed by ® are registered trademarks of DuluxGroup (Australia) Pty Ltd ABN 67 000 049 427. Marks followed by the symbol ™ are trademarks.

Please note that this document is only valid for 60 days from the date of issue.

DuluxGroup (Australia) Pty Ltd 1956 Dandenong Road, Clayton, Victoria 3168 AU ABN 67 000 049 427