

AUIN00050 Intergrain Industrial Solvent Based Tannin Blocker White

Introduction

Part A
702W0498

Description and Image

Intergrain Industrial Solvent Based Tannin Blocker is an opaque tannin blocker, which prevents tannin rich timbers from leaching tannins and protects from UV during construction

Features and Benefits

- Prevents tannin rich timbers from leaching tannins
- Resistant to UV

Uses

Interior and exterior timber joinery, windows and doors

Performance Guide

Weather
Not designed as a finish coat.

Typical Properties

Heat Thinner
Mineral turpentine

Colour
White

Number of Coats
1-2

V.O.C. Level
<420g/l

Meets GBCA V.O.C. Requirements?
No

Touch Dry
45 minutes

Clean Up Description
Mineral turpentine.
To avoid spontaneous combustion of contaminated application cloths, soak application cloths in water or immediately spread used application cloths flat in a cool, well ventilated area to dry completely before disposal. Do not scrunch up or place cloths on top of each other.

Application Methods

 **Brush**  **Roller**  **Spray**

Application Conditions

Solids by Volume

48

	Min	Max	Recommended
Wet Film Per Coat (microns)	<input type="text"/>	<input type="text"/>	84
Recoat Time (min/hours)	1.5 hours	<input type="text"/>	<input type="text"/>
Theoretical Spread Rate (m ² /L)	<input type="text"/>	<input type="text"/>	12

Typical Property Notes

Coverage

Approximately 12m²/L, depending on the porosity of the timber.

Dry times

All timings quoted at 25°C and 50% relative humidity. Cold or humid conditions may require longer. Dry times also subject to film thickness and airflow.

Touch dry: 45 minutes.

Recoat: 1.5 hours minimum.

Application Guide

Surface Preparation

Ensure surface is dry and free from dirt, dust, grease, oil and loose material. Sand to a smooth surface if necessary. Remove all sanding dust.

Application Procedure and Equipment

Apply 1-2 coats using brush, roller or spray equipment. If spraying, the product can be thinned with mineral turpentine, as required, to suit spray equipment.

Health and Safety

SDS Number

DLXGHSEN004030

SDS Link

[View SDS Link](#)

Using Safety Precautions

Flammable liquid and vapour. Causes skin irritation. May cause drowsiness or dizziness.

Keep out of reach of children. Read carefully and follow all instructions. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting and all other equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid breathing dust, fume, gas, mist, vapours or spray. Wash hands, face and all exposed skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing including eye/face protection and suitable respirator.

Spills & leaks: Clear area of all unprotected personnel. Slippery when spilt. Wear protective equipment. Absorb with sand or soil. Collect and seal in properly labelled drums. Refer to State/Territory Land Waste Management Authority for disposal.

Please refer to SDS Link. In case of emergency, please call 1800 220 770.

Transport and Storage

Pack A

702W0498

Size:

15L

Weight:

22kg

Please refer to the Safety Data Sheet for full safety, health and transportation information.

Disclaimer

This Data Sheet is copyright to DuluxGroup (Australia) Pty Ltd and/or DuluxGroup (New Zealand) Pty Ltd (collectively, 'Dulux'). It may not be varied or altered without the prior written consent of Dulux, and if it is, Dulux has no responsibility or liability for those variations.

Unless Dulux has provided you with a customised, project-specific specification, this Data Sheet does not represent that any particular product or product system will be suitable for your project.

Any information provided in this Data Sheet is given in good faith and is believed by Dulux to be correct at the time of publication. Products and coating systems can be expected to perform as indicated in this Data Sheet, provided the substrate is in good condition, the coatings are applied by a suitably experienced and skilled applicator, and the preparation, application and maintenance is followed strictly as set out in this Data Sheet, and as recommended on the applicable Safety Data Sheets for the relevant products, available from www.duspecplus.com.au. Climatic conditions at application time can affect product suitability and performance.

The correct colour or colour match is the responsibility of the applicator. Colours will change over time and Dulux does not guarantee that the same colour newly mixed will match a colour applied earlier which has been subjected to weathering or other change elements. No product colour is guaranteed against colour change.

Where any liability of Dulux in respect of this Data Sheet cannot by law be excluded, Dulux's liability is limited, as permitted by law and at Dulux's option, to resupply of the relevant products or services or to reimbursing the cost of those products or services.

WHERE LEAD MAY BE PRESENT: The asset manager is responsible for verifying the presence of lead and determining whether to remove or encapsulate the lead. If lead is present, the work must be done in strict accordance with AS 4361 Parts 1 and 2 and Worksafe Australia guidelines.